

## SNV/U High Performances UV Microchip Series

### Key features

- ▶ 355nm and 266nm
- ▶ Repetition rate up to 20kHz
- ▶ Ultrashort pulses down to 550ps
- ▶ Multi-kW peak power
- ▶ Excellent beam quality
- ▶ Efficient, air-cooled
- ▶ Sealed package, extremely long life



For generating high peak power ultraviolet pulses of a few hundred picoseconds, microchip lasers are economical, compact, and reliable. Micro-joule UV pulses are generated by harmonic conversion of the IR passively Q-switched Nd:YAG engine. Microchips are also easy to operate and service ; controllers can be used with every laser head model and swapped within minutes while conserving constant performances.

The SNV and SNU series are designed for high average power, delivering multi-kW peak power at repetition rates up to 20kHz.

### Applications

- ▶ Semiconductor inspection
- ▶ Laser-induced fluorescence (LIF)
- ▶ Micro dissection
- ▶ Organic compound marking and micromachining
- ▶ Biohazard detection
- ▶ Time resolved fluorescence
- ▶ Laser Induced Breakdown Spectroscopy (LIBS)

For your application, find your pulsed laser solution

**teem** photonics™

**Technical specifications:**

	<b>SNV-05P-100</b>	<b>SNV-20F-100<sup>(7)</sup></b>	<b>SNU-02P-100</b>	<b>SNU-20F-100</b>
<b>Wavelength</b>	355nm	355nm	266nm	266nm
<b>Repetition Rate</b>	>5kHz	>19kHz	>6kHz	>19kHz
<b>Constant Pulse width range (FWHM) <sup>(1)</sup></b>	<0.6ns	<0.6ns	<0.6ns	<0.6ns
<b>Output power<sup>(2)</sup></b>	>5mW	>10mW	>2mW	>10mW
<b>Output energy</b>	>0.5μJ	>0.5μJ	>0.3μJ	>0.5μJ
<b>Peak Power</b>	>0.7kW	0.7kW	>0.5kW	>0.7kW
<b>Short term (1min) power stability <sup>(3)</sup></b>	<±1%	<±1%	<±1%	<±2%
<b>Long term (6 hrs) power stability<sup>(3)</sup></b>	<±5%	<±5%	<±5%	<±5%
<b>Beam profile</b>	Gaussian TEM00	Gaussian TEM00	See note (5)	See note (5)
<b>Full angle divergence Horizontal@1/e<sup>2</sup> Vertical@1/e<sup>2</sup></b>	8.5±2mrad 6±2mrad	11±2mrad 7±2mrad	11±2mrad <1.5mm <sup>(6)</sup>	11.5±2mrad 0.65±0.25mrad
<b>M<sup>2</sup><sup>(4)</sup></b>	<1.3	<1.3	<1.3	<1.4
<b>Gaussian fit in far field</b>	N/A	N/A	N/A	>85%
<b>Polarization</b>	Linear PER>20dB	Linear PER>20dB	Linear PER>20dB	Linear PER>20dB
<b>Package dimensions</b>	180x55x36mm	186x60x36mm	180x55x36mm	210x60x36mm
<b>Package weight</b>	400g	500g	400g	500g
<b>Options (table p3)</b>	C	C	C	C
<b>Options included</b>	-	S	-	S

**Notes**

<b>(1)</b>	Measured with 1Ghz photodiode and 1GHz/10GS/s oscilloscope.
<b>(2)</b>	Measurement performed with an OPHIR thermal power sensor (OPHIR 3A-FS-SH)
<b>(3)</b>	For temperature variation < ± 3°C and < 3°C/hour, stability is measured with calorimeter - detector band [DC, 2Hz]
<b>(4)</b>	Mean average value M = √(XY), X and Y being respectively the major and minor axis of the ellipse
<b>(5)</b>	Beam exhibits different profile in horizontal (Gaussian) and vertical ((sin x /x) <sup>2</sup> in far-field) plan
<b>(6)</b>	5%/95% diameter, at 300mm from laser output
<b>(7)</b>	Contact factory for availability

For your application, find your pulsed laser solution

**teem** photonics™

**Complementary information & options:**

**Environment Parameters**

<b>Operating Temperature Range</b>	15-35°C
<b>Maximum Laser Head Baseplate Temperature</b>	<50°C
<b>Maximum Power Consumption</b>	<40W
<b>Laser Head Thermal Dissipation</b>	<15W
<b>Storage Temperature</b>	0-50°C
<b>Shock of 11ms according to IEC 68-2-27, non operating</b>	25g
<b>Vibration 5Hz to 500Hz sinusoidal according to IEC 68-2-6</b>	2g

**Certification**

<b>Laser classification according to IEC 60825-1:2007</b>	3B for SNV-05P and SNV-20F 4 for SNU-02P and SNU-20F
<b>CDRH</b>	Yes, if used with a -DR1 controller
<b>ROHs</b>	Yes

**Options**

<b>Collimation (C)</b>	With collimated beam
<b>Synchronization output (S)</b>	TTL compatible output signal for synchronization/monitoring


**Available Controller Types**

<b>Model</b>	<b>Type</b>	<b>Input Power</b>	<b>CDRH</b>
MLC-03A-DR1	Desktop	100-240 V AC	Yes
MLC-03A-MR1	Module	12 V DC	No
MLC-03A-BR1	Board	12 V DC	No

For your application, find your pulsed laser solution

**teem** photonics™

**CDRH Laser Head Mechanical Drawings : SNV-05P-100**




Notes: All dimensions are in millimeters  
Third angle projection

For your application, find your pulsed laser solution

teem photonics™


**CDRH Laser Head Mechanical Drawings : SNV-20F-100**



For your application, find your pulsed laser solution

**teem** photonics™

**CDRH Laser Head Mechanical Drawings : SNU-02P-100**



Notes: All dimensions are in millimeters  
Third angle projection

For your application, find your pulsed laser solution

**teem** photonics™

**CDRH Laser Head Mechanical Drawings : SNU-20F-100**

